



100% VISCOSE RAYON BROIDERY THREAD

Duravis®

DURAK Duravis® is a high-quality continuous filament viscose rayon broidery thread, specially produced for broidery machines. It provides excellent performance even on high-speed embroidery machines. Thanks to its natural structure, it offers a soft touch where the embroidery contacts the skin. It delivers vivid and brilliant colors. DURAK Duravis® is suitable for a wide range of applications, thanks to its bright and ample color options, thickness variations, and outstanding broidery performance.



Areas of Use

- ✦ Broidery
- ✦ Apparel
- ✦ Underwear
- ✦ Home Textiles

Product Properties

- ✦ Reliable and soft embroidery thread with a natural appearance.
- ✦ High color fastness.
- ✦ Vivid and brilliant appearance.
- ✦ Offers a feel and texture similar to natural fibers.
- ✦ Works extremely smoothly.

Duravis®

Storage Conditions

Must be stored away from heat, humidity and direct sunlight.

Points to consider

Embroidered products made with Visco are washable.

However, in order to maintain color fastness, the following points should be observed during washing.

- 1- Embroidered items should be washed separately and not together with other products.
- 2- They should not be placed tightly in the washing machine, as the embroidered items need to move freely inside the drum.
- 3- Embroidery products should be shaken immediately after washing, and should not be left folded or stacked when wet and damp.
- 4- Embroidered items (that do not contain chemical mixtures) should be washed with mild detergents. Harsh chemicals and bleach may cause discoloration of the embroidery.
- 5- Embroideries on woolen fabrics should not be machine washed and should not be shaken.
- 6- Stain removers or bleaching products should not be used.
- 7- Embroideries made of viscose can be dry-cleaned.
- 8- Ironing should be done on the reverse of the embroidered surface or on another fabric. During ironing, use the lowest possible temperature and a steam iron instead of a damp cloth.
- 9- Due to environmental regulations and measures for nature protection, some materials used in dyes and paints are periodically changed. Therefore, despite all efforts, slight differences may occur between the color chart and the final product.

Thickness and Strength Chart

Ticket No.	Nominal Tex	Strength CN	Elongation %	Needle Size (Nm)
50/1*2	10	300	15 - 20	*
80/1*2	16	360	15 - 20	*
120/1*2	24	620	15 - 20	*

Color Fastness

Washing fastness at 60°C	ISO 105 C06	Min. 4
Water fastness	ISO 105 E01	Min. 4
Rubbing fastness	ISO 105 X12	Min. 4
Dry cleaning fastness	ISO 105 D01	Min. 4
Perspiration fastness	ISO 105 E04	Min. 4
Light fastness	ISO 105 B02	Min. 4

Product Options

Durak Duravis® offers a wide range of colors in a variety of meter sizes and thicknesses.

